

CS Promotions, LLC
2023 Old School/ 85 and Newer Rules/ Mini Vans
Chad Anderson 402.992.0318 or Shawna Anderson 402.992.0231
Mike Korth 402-841-1465

This is a generic set of rules for the 85 & Newer (Old School) & Mini Van Classes. These two classes are separate and will not run together. Cars run with cars & Vans run with Vans.

- ALL RULES WILL BE FOLLOWED, OR YOU WILL NOT RUN
- All drivers must sign the driver's paperwork, or they will not drive in the event
- All drivers and crew members must attend the drivers meeting
- No hot rodding in the pits, keep it at an idle. This will be the quickest way to be DISQUALIFIED
- You are given 1 minute to make an aggressive hit. After 1 minute that particular car will be disqualified. You are only given 1 minute in total, not 1 minute to get started and 1 minute to hit
- No drivers are allowed alcohol period. If you are wearing a drivers band and drinking any form of alcohol-YOU WILL BE DISQUALIFIED
- Cars will be re-inspected before any prize money is paid out. The cars will be re-inspected by the Tech staff only. Everyone else will stay back until cars are deemed to be legal
- Any complaints that a driver has about another car prior to the start of the first heat will need to be addressed in the drivers meeting in specifics. If nothing is said, we don't want to hear about it after the show
- **Any questions, ABOUT these rules call us... If it does not say you can do it THEN DON'T. We can't stress enough to call first**
- Judges decisions are FINAL!!!

1. Must be a 1985 or newer car/minivan that has a 4 cylinder or 6 cylinder engine NO 8 Cylinder engines allowed. (NO AWD, VOLVO, SUBARU, ASTRO VANS, OR CROSSOVER SUV'S ALLOWED) NO FULL FRAME CARS/MINIVANS ALLOWED. MUST BE UNI-BODY STYLE CHASSIS!
2. Must be the original engine in the car (no modifications of any kind).
3. Must remove all outside body chrome, bumper covers, headlights, tail lights, turn signals and windows (all glass and plastic objects); this includes all window tar with glass particles. You Must also remove all interior pieces not needed (carpet, back seat, headliner, plastic trim, etc.) These items are a fire hazard & safety issue.

CS Promotions, LLC
2023 Old School/ 85 and Newer Rules/ Mini Vans
Chad Anderson 402.992.0318 or Shawna Anderson 402.992.0231
Mike Korth 402-841-1465

4. Must relocate battery to inside of cab and must be securely fastened, on front passenger side floor. Battery in engine compartment must be removed. If the Vehicle came from the factory with the battery in the rear seat compartment it may stay as long as it's securely mounted & covered.
5. Must **REMOVE** all air bags & air bag cylinders in driver's & passenger compartment. Along with side curtain & seat belt air bags!
6. You must run an aftermarket or homemade fuel tank in the rear seat area. 8 gallon maximum. This aftermarket tank is allowed to be mounted on the rear floor area or off of the back seat bar. The gas tank must be made of steel, stainless steel, or aluminum (no plastic tanks allowed) you are allowed to fabricate a "gas tank protector" but must remain a minimum of 12" from the doors, 10" from the speaker deck, and 8" off the floor.
7. **You must put in a rear seat bar (mandatory) from driver's side to passenger side, behind seat. Welded or bolted (seat bar MUST be welded in if a aftermarket fuel tank is attached to it) with 3" minimum bar sizes, must have endplates on both ends (4"X 4") minimum. Rollover bar must also be used (mandatory) this rollover bar may extend on the exterior of the roof or on the inside of the roof and must run vertical and not angled forward or backward, this rollover bar can be welded or bolted to your "backseat" bar or floor tin. Rollover bar must also be welded, bolted, or #9 wired to the roof sheet metal.**
8. Front dash must remain in the car and cannot be removed.
9. Must use factory gas pedal, shifter, brakes, steering wheel. Everything must be factory for year, make, and model of car.
10. Must chain or #9 wire the doors shut in 1 spot only. Trunk and hood must be chained or #9 wired in 4 spots only. Front window opening must have chain or #9 wire in 3 spots to keep the hood from coming through window opening. HOODS MUST BE OPEN FOR INSPECTION
11. **MANDATORY** Driver's door must have one outside reinforcement safety plate (max ¼" thickness by 12" wide **minimum** & must lay flat on the door no channel iron, angle iron, or grader blades allowed) securely bolted or welded to outside of driver's door and not to exceed 6" beyond vertical door seams.

CS Promotions, LLC
2023 Old School/ 85 and Newer Rules/ Mini Vans
Chad Anderson 402.992.0318 or Shawna Anderson 402.992.0231
Mike Korth 402-841-1465

12. Must have factory rims, you are allowed small centers but NO BIG CENTERS. Trailer, Mud and skid loader tires are allowed. No bigger than 16" tires are allowed. You are allowed two doughnut tires only. You may tube your tires but NO FOAM FILLED OR DOUBLED TIRES!

13. You must remove plastic bumper skins. **NO body shaping or square-off fenders.** May bend down hoods in the front. No Tucking of the trunk, you are allowed to completely remove the trunk lid. Notching of the rear frame is allowed but no pre-bending!

14. You will be allowed to replace the stock front bumper with a piece of 3"x3"x 3/16" thick square tube, ends of tube must be open and nothing else will be allowed inside. Tube must not exceed 6" outside of the exterior of the frame rails on both sides. This tube must remain completely straight and have no point or shape to it. This "Aftermarket" bumper can be welded on the front side of the frame rails (no shorting of frame rails) with one 1/2" wide weld bead all the way around. STOCK BUMPERS THAT CAME OFF ANY OTHER CAR IS ALLOWED BUT MUST HAVE AN OPENING FOR INSPECTION ON BOTH ENDS AND MUST NOT EXCEED 6" OUTSIDE OF THE EXTERIOR OF THE FRAME RAIL ON BOTH SIDES. NO STUFFED BUMPERS ARE ALLOWED. OR THE ABOVE 3" TUBE AS MENTIONED ABOVE. If running the stock bumper you will still be allowed to weld the bumper on with the same 1/2" wide weld bead. NO ADDED MATERIAL TO ATTACH BUMPERS!

15. You will be allowed (2) 5/8" bolts or pieces off all-thread as hood bolts. These two "hood bolts" must only be welded to the sheet metal tin on the top side of the radiator support. On the top side of the hood you will be allowed a 3" washer to hold the hood down.

16. YOU MUST HAVE AT MINIMUM (2) 8" HOLES CUT IN THE HOOD FOR FIRE CONTROL!

This is a "knock the windows out and run" class--any extra modifications will result in disqualification.

THE ONLY WELDING ALLOWED IS A PLATE ON THE EXTERIOR OF THE DRIVERS DOOR, BACK SEAT BAR, GAS TANK PROTECTOR, FRONT BUMPER, HOOD BOLTS & ROLLOVER BAR! IF ANY OTHER WELDING IS FOUND YOU WILL NOT HAVE A CHANCE TO CUT IT, YOU WILL NOT RUN.

CS Promotions, LLC
2023 Old School/ 85 and Newer Rules/ Mini Vans
Chad Anderson 402.992.0318 or Shawna Anderson 402.992.0231
Mike Korth 402-841-1465

Disclaimer to car builders and drivers: IF IT DOES NOT SAY YOU CAN DO IT WITHIN THESE RULES, DO NOT DO IT. ALL CARS FOUND TO BE ILLEGAL WILL NEED TO BE CORRECTED TO PASS OFFICIALS INSPECTION, CARS THAT DO NOT PASS INSPECTION WILL NOT RUN AND HAVE TO BE LOADED. ALL JUDGES DECISIONS ARE FINAL MEANING: IF YOU OR YOUR PIT CREW WANT TO CHOOSE TO ARGUE WITH ANY OF THE JUDGES BEFORE, DURING OR AFTER THE DERBY YOU WILL BE DISQUALIFIED AND POSSIBLY ESCORTED OUT OF THE EVENT. THIS IS A FAMILY EVENT AND YOU MUST BE RESPECTFUL AT ALL TIMES.

ALL DECISIONS BY OFFICIALS ARE FINAL!

CS PROMOTIONS